

Dimensions				
Notes			Specified value	Measured value
	Wheelbase	mm	2580	
Tightening torques				
Notes			Specified value	Measured value
	Tightening torque - steel wheels		80 Nm	
	Tightening torque - alloy wheels		80 Nm	
	Trackrod locknut/clamp		45 Nm	
Checking range - Front wheels				
Notes			Specified value	Measured value
	Load positioning		Unladen	
39	Ride height reference table			
	Toe-in (N = negative, toe-out)	mm	1 - 3	
	Toe-in	deg	0°9' - 0°27'	
	Toe-in	deg-1/100	0,15 - 0,45	
	Camber	deg	0°55'N - 0°5'P	
	Camber	deg-1/100	0,92N - 0,08P	
	Castor	deg	3° - 4°	
	Castor	deg-1/100	3 - 4	
Setting data - Four wheels				
Notes			Specified value	Measured value
	Load positioning		Unladen	
39	Ride height reference table			
	Toe-in (N = negative, toe-out)	mm	2±1	
	Toe-in	deg	0°18'±9'	
	Toe-in	deg-1/100	0,30±0,15	
	Camber	deg	0°25'N±30'	
	Camber	deg-1/100	0,42N±0,50	
	Camber adjustment		Not adjustable	
	Castor	deg	3°30'±30'	
	Castor	deg-1/100	3,50±0,50	
	Castor adjustment		Not adjustable	
	KPI (SAI)	deg	11°15'±30'	
	KPI (SAI)	deg-1/100	11,25±0,50	
	Included angle	deg	10°50'	
	Included angle	deg-1/100	10,83	
	Rear toe-in	mm	4,20±1	
	Rear toe-in	deg	0°38'±9'	
	Rear toe-in	deg-1/100	0,63±0,15	
	Rear toe-in adjustment		Not adjustable	
	Rear camber	deg	1°20'N±15'	
	Rear camber	deg-1/100	1,33N±0,25	
	Rear camber adjustment		Not adjustable	

**Autodata Note 39**

<b>H1</b>	<b>H2</b>
145 mm	145 mm

Fig.74845

**Autodata Note 39**

<b>H1</b>	<b>H2</b>
145 mm	145 mm

Fig.74845

